










Extruded heatsinks for PCB mounting

for semiconductor screw-mounting

	  ... STS			  ... STIS			  ... STSB		
art. no.	H [mm]	R _{th} [K/W]							
SK 104 25,4 ...	25.4	14	TO 220/ SOT 32/ TO 3 P						
SK 104 38,1 ...	38.1	11	TO 220/ SOT 32/ TO 3 P						
SK 104 50,8 ...	50.8	9	TO 220/ SOT 32/ TO 3 P						
SK 104 63,5 ...	63.5	8	TO 220/ SOT 32/ TO 3 P						
please indicate:									
... mouting method									
STS =with solder pin									
STIS =with solder pins and insulating washer									
STSB=with threaded bolt M 3, brass									

E = mounting method
special lengths and transistor drillings on request
surface treatment: black anodised

horizontal for semiconductor screw-mounting

									
art. no.	l [mm]	R _{th} [K/W]	⌀						
SK 104 25,4 LS	25.4	14	TO 220/ SOT 32/ TO 3 P						
SK 104 38,1 LS	38.1	11	TO 220/ SOT 32/ TO 3 P						
SK 104 50,8 LS	50.8	9	TO 220/ SOT 32/ TO 3 P						

special lengths and transistor drillings on request
surface treatment: black anodised