



LED POWER SUPPLY DATASHEET

SNP4-350ILP

DESCRIPTION

High Cost Performance, SELV, Open circuit, short circuit, overload and over temperature protection, Compliance to ERP directive, lifetime 30,000hrs.

M M 110 SELV

Input

Items	Conditions	Request	Note
Input voltage	Ta	AC100-240V	--
Input frequency		50-60Hz	--
Input current	°C	<0.15A	--
Input power	25 ,rated input voltage, output with max. rated power	<6.5W	--
Efficiency		≥78%	--
Standby	25 ,rated input voltage, output without load	<0.3W	average
Inrush current	25 ,rated input voltage	<60A	peak
PF	25 ,rated input voltage, output max. rated power	≥0.40	--

Temperate and others

Item	Conditions	Request	Note
Operation temp.	--	-20℃~50℃	--
Relative humidity	--	45%~90%	--
Max. case temp.	--	85℃	<90℃
Lifetime	Max.Ta,rated input voltage,output with max.rated power	30,000hr	--
Working noise	25 ,rated input voltage,output with rated power ,mute box background noise<35dB,pickup 10cm distance from products	--	--

Protection

Items	Conditions	Request	Note
Open circuit	Ta ,rated input voltage, no load	yes	--
Over load	Ta ,0.94-1.06 times of input voltage, 1.2 times of rated power	yes	--
Short circuit	Ta ,0.94-1.06 times of input voltage	yes	--
Over temperature	Ta ,0.94-1.06 times of input voltage, temperature detected pointed more than 115 degree	yes	--
Over voltage	Ta ,0.94-1.06 times of input voltage,output voltage is 1.5 times of rated one	--	--
Auto recovery	Over load, short circuit revocation	yes	--
Latch off	Over voltage, over heat re-start after cut off	--	--

Output

Items	Conditions	Request	Note
Startup time	25 ,rated input voltage,output with max. rated power	<2S	--
Output voltage and precision	Ta ,rated input voltage, output with rated power	--	--
Output current range	Ta ,rated input voltage	--	--
Output voltage wave	25 ,rated input voltage,output with max. rated power	--	Vp-p
Output overload	25 ,rated input voltage,output with 2 times LED load	--	--
Output current and precision	Ta ,rated input voltage, output with rated power	350mA±10%	--
Rated output voltage range	Ta ,rated input voltage,	3~12V	--
Output current wave	25 ,rated input voltage,output with max. rated power	50mA	Irms
Dimming mode	--	--	--
Dimming range	--	--	--

Mechanical, mounting

Items	Conditions
Case material and size	Plastic
Mounting ways	Independent
Insulation type	Class II
IP grade	IP66
Input cables dimension	
Output cables dimension	
Output cables length	200mm

Standard

Items	Conditions
Safety	IEC61347-1、IEC61347-2-13、UL8750
Harmonic	IEC61000-3-2
EMI	IEC55015、FCC PAR15
EMS	IEC61547

Dimensions(mm)

