Note: This datasheet may be out of date

Please download the latest datasheet of TZW4Z1R5A001R00 from the official website of Murata Manufacturing

https://www.murata.com/en-sg/products/productdetail?partno=TZW4Z1R5A001R00

### TZW4Z1R5A001R00










### Appearance & Shape







### **Features**

- 1. To meet high power application due to withstanding voltage 550Vdc.
- 2. Extremely high self-resonant frequency. (More than 3GHz at rated C max.)
- 3. Typical application: Impedance matching for Cellular Base Station.
- 4. High Q value in more than VHF, UHF and Microwave bands. (More than 200 in 500MHz, C max.)
- 5. Available for pick and place machine. Possible thinner design due to 2.6mm low profile.
- 6. Non-electrical contact construction (rotor as middle electrode) provides high reliability.
- 7. Compact size: 4.2(W)x5.2(L)x2.6max.(H)mm.



## Packaging Information

Packaging	Specifications	Minimum Order Quantity
R00	180mm Embossed Tape	500

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/12/12

Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ TZW4Z1R5A001R00 \ from \ the \ official \ website \ of \ Murata \ Manufacturing } }$ 

 $\underline{\text{Co., Ltd.}}\\ \text{https://www.murata.com/en-sg/products/productdetail?partno=TZW4Z1R5A001R00}$ 

# TZW4Z1R5A001R00



Shape	SMD	
Operating Temperature Range	-55°C to 125°C	
Thickness	2.6mm	
Thickness Tolerance	max.	
Rated Voltage	250Vdc	
Cmin.(max.)	0.4pF	
Cmax.	1.5pF	
Cmax. Tolerance	+100/-0%	
Adjustment Direction	Тор	
тс	NP0±150ppm/°C	
Q	200min. at 500MHz, Cmax.	
Withstanding Voltage	550Vdc	
Insulation Resistance(min.)	10000ΜΩ	
Torque	1.5 to 10.0mNm	
Mass	0.15g	

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/


Last updated :2018/12/12


Note: This datasheet may be out of date  $\underline{ Please \ download \ the \ latest \ data sheet \ of \ TZW4Z1R5A001R00 \ from \ the \ official \ website \ of \ Murata \ Manufacturing } }$ 

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-sg/products/productdetail?partno=TZW4Z1R5A001R00} \\$ 


# TZW4Z1R5A001R00







Constructions



Temp. Coeff. Characteristics

Frequency Characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/12/12